



Pay2Print Kiosk

High Performance

High Performance Touch Panel PC dedicated to kiosks.

Recent Technology

Equipped with the most recent technologies, operating on the latest INTEL Celeron processor.



Pharos Systems offers a solution that enables customers to track, monitor, audit, and control their print and copy assets to reduce waste, optimise performance, guide the purchase of new devices and make the most of existing ones.

Emos-Infineerbrings “added value” to Pharos by offering the user the ability to add monies to their account via a self service Kiosk, resulting in lower administration costs and giving the user more control over their account.

Overall dimensions:

W: 450mm x D:245mm X H: 828mm

- The new Pharos Pay2Print Kiosk offers a user friendly means of self service account revaluation
- Smart 15" Touch screen kiosk
- Full colour displays that are easily navigated
- Users can top-up their account quickly and efficiently making it ideally suited for a busy school or univeristy
- Provides out-of-hours account revaluation and minimises staff involvement
- Note and coin configuration, accepting up to 6 different coins and 4 banknote denominations
- Software allows the administrator to manage the device remotely
- Full range of cusotmised reports available
- Easy to configure and update from your back office

Features:

Dust and Waterproof display front (IP65)

Robust and rugged metal housing

Very slim (50mm) to save space and provide a sleek finish and space savings

VESA - type mounting holes/brackets

Can be placed horizontally or wall mounted

Multiple Communication Ports

Model	TEOS1513
Motherboard	B78
Processor	Intel Celeron M 1.3 GHz
Chipset	Intel 852GM+ICH4
System Memory	1 X DDR SO-DIMM socket supported with memory size 512K Up to 2GB
LCD Touch Panel	
LCD size	15" TFT LCD
Brightness	350 cd /m ²
Maximal resolution	1024 x 768
Touch Screen Type	Resistive
Storage	
HDD	40GB –2.5"
Connector	Compact Flash Card slot/connector option (replaces the hard disk)
Expansion Slots (Slots PCI)	1 x mini Slot PCI
Expansion	
Mini—PCI Socket	1
Communication Ports	
USB	4 x USB (V2.0)
Serial/COM	4 Serial ports (com RJ-45; com2 configurable to RS422/485; com3 & COM4 self powered –9pin (5V OR 12V)
Parallel/Printer	1 x DB25 connector
LAN (10/100)	1 X RJ-45
Audio	1 x lineout, 1 x line in
External Power Adapter	1 x DC 19V, 90W
VGA	1 output to connect a 2nd screen
Environmental Information	
Safety & EMC	CE, FCC Class A, LVD, RoHS
Operating temperature	0° to 45° C (32°F to 140° F)
Dimensions (W x D x H)	368 x 293 x 57
Weight	6.8kg
Mounting	100mm x 100mm
OS Support	Win XP Pro, XPe, WEPOS, Windows NT4.0 / 2000, Linux